

ver. 20200404 Rev 0

year: **2022**  
code: **2670602A70100**  
type: **floor lamp**  
application: **indoor**



## Technical data


Light source	LED
Circuit structure	LED strip
Light emission direction	diffused
Power	69 W
Source lumens	7866 lm
Source efficacy	114 lm/W
Energy class	F
Delivered lumens	6158 lm
Secondary	24 V
Colour temperature	3000 K / variants page 2
Colour rendering index	90 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Safety class	II
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○

## Optional

Emergency mode	<input type="checkbox"/>
Motion sensor	<input type="checkbox"/>
Directional	<input type="checkbox"/>


## Packing

Net weight
Packaging 1
Packaging 2
Packaging 3
Packaging 4
Packaging 5



## Technical drawing

Size	ref. image mm - inch
------	----------------------



## Structure

Material	aluminium
Finish	white / variants page 2

## Diffuser

Material	polymer stretch
Finish	opal / variants page 2

## Electronics / Driver

Included	Yes
Quantity	1
Voltage	100-120V 60 Hz

**Dimmable**



## Hanging cables

Stainless steel cables standard length (custom available)	-
Electric cable standard length (custom available)	-

## Warranty

Duration	2 years
----------	---------

# LUNA F900 DIMMER 110V

ver. 20200404\_Rev\_0

year: **2022**

code: **2670602A70100**

type: **floor lamp**

application: **indoor**

## Available variants

### Colour temperature

2700 k



3000 k



3500 k



4000 k



custom



### Colour rendering index

CRI 80



CRI 90



CRI 95



custom



### Structure finish

gold / brass



matt white



matt black



embossed white



embossed black



custom



### Diffuser / Optical

opal



custom



### Ceiling Mount

remote driver



custom

