



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Pacific LED Vanity PCV Series



### Features

Contemporary style vanity with endcaps and smooth white diffuser provide a simple and clean appearance. Fixture can be mounted horizontally or vertically to a standard junction box (not included).

### Construction

The wiring channel is formed from 22-gauge steel and is provided with standard mounting holes and wiring access.

### Finish

Housing is finished in lighting grade baked gloss white enamel paint. Satin Nickel endcaps.

### Diffuser

Diffuser assembly consists of metal endcaps with a plated satin nickel finish. Diffuser is .07" thick smooth white acrylic. Diffuser ends attach with thumb screws.

### Electrical

Input 120VAC / 60Hz  
Not compatible with dimmers.

### LED

Integrated LED modules capable of producing:  
17W = 1800 source lumens, 1392 delivered lumens  
25W = 2700 source lumens, 2086 delivered lumens  
34W = 3600 source lumens, 2892 delivered lumens  
3000K (CCT), 80 CRI. Rated for 50,000 hrs. LED life.

### Certification

All fixtures are cETLus listed for damp locations.  
ADA  
ENERGY STAR® Qualified

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.


**Specifications and dimensions  
subject to change without notice.**



24"



36"



## Ordering Information:

Satin Nickel	LED	Source Lumens	Delivered Lumens	CCT	L	H	D	MC
PCV241700L30SN	17W	1800	1392	3000K	24"	6"	3-1/8"	15-5/16"
PCV362500L30SN	25W	2700	2086	3000K	36"	6"	3-1/8"	26-3/4"
PCV483400L30SN	34W	3600	2892	3000K	48"	6"	3-1/8"	38-3/4"