



| | | |
|----------------|--|--------------|
| LOCATION | | DATE |
| PREPARED BY | | QUANTITY |
| COMMENTS | | FIXTURE TYPE |
| CATALOG NUMBER | | |

Tad LED Sconce TADS Series

Features

Contemporary sconce with square metal base. Ideal use for general lighting in indoor residential, commercial, and hospitality applications. Fixture can be mounted horizontally or vertically to a standard junction box (not included).



Construction

Fabricated metal housing. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black or Satin Nickel.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC 60 Hz.

LED

Integrated LED modules capable of producing:
 12W = 1100 delivered lumens
 Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
 Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for indoor damp locations.
 ADA Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

**Specifications and dimensions
 subject to change without notice.**



Ordering Information:

| Black | Satin Nickel | LED | Delivered Lumens | Adjustable CCT | H | W | D |
|------------------|------------------|-----|------------------|-------------------------------|-----|--------|----|
| TADS0514LAJMV BK | TADS0514LAJMV SN | 12W | 1100 | 2700K/3000K/3500K/4000K/5000K | 14" | 4-1/2" | 4" |