



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Features

Perimeter illumination top and bottom.
Includes 9 ft. adjustable cable.
Available in single or double sphere.
For use in kitchen, dining, foyers
or anywhere general lighting is needed.
Provides lighting in residential,
commercial and hospitality applications.
This fixture mounts to a standard
junction box (not included).

Construction

Extruded aluminum housing.
The canopy fits over a standard junction box.
Power supply connections must be made inside
a junction box (not included).

Finish

Black, Light Antique Brass or Satin Nickel.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and
commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120 VAC.

LED

Integrated LED modules capable of producing:
24 in. Single - 20W = 740 delivered lumens
32 in. Single - 30W = 1000 delivered lumens
24/32 in. Double - 50W = 1780 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in
materials and workmanship for a period of
5 years from date of purchase.

Specifications and dimensions
subject to change without notice.



Ordering Information:

Single

Black	Light Antique Brass	Satin Nickel	LED	Delivered Lumens	Adjustable CCT	H	DIA. 1
OBRP24LAJUDBK	OBRP24LAJUDLB	OBRP24LAJUDSN	20W	740	2700K/3000K/3500K/4000K/5000K	1-1/2"	24"
OBRP32LAJUDBK	OBRP32LAJUDLB	OBRP32LAJUDSN	30W	1000	2700K/3000K/3500K/4000K/5000K	1-1/2"	32"

Double

Black	Light Antique Brass	Satin Nickel	LED	Delivered Lumens	Adjustable CCT	H	DIA. 1	DIA. 2
OBRP2432LAJUDBK	OBRP2432LAJUDLB	OBRP2432LAJUDSN	50W	1780	2700K/3000K/3500K/4000K/5000K	1-1/2"	32"	24"