



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Patton LED Outdoor Sconce PATW Series

Features

Ideal use for general lighting in outdoor residential, commercial, and hospitality applications. Fixture can be mounted to a standard junction box (not included).

Construction

Polycarbonate housing and painted in weather resistant powder coating. Power supply connections must be made inside a junction box (not included).

Finish

Black, Textured Grey or Oil-Rubbed Bronze finish.

Diffuser

Frosted Polycarbonate diffuser.

Electrical

Input 120 VAC / 60Hz.

Minimum starting temp -4° F/-20° C

Integrated photocell for dusk to dawn operation.

LED

Integrated LED modules capable of producing:

12W = 900 delivered lumens

Adjustable Choice 3000K, 4000K, 5000K (CCT).

Rated for 50,000 Hrs. 80 CRI.

Certification

All fixtures are cETLus listed for outdoor wet locations.

ADA

Title 24/JA8 Compliant

Ideal for coastal applications (IP65)


Warranty

5 Year Limited Warranty:

Restrictions apply based on location.

Specifications and dimensions

subject to change without notice.



Ordering Information:

Black	Textured Grey	Oil-Rubbed Bronze	LED	Delivered Lumens	Adjustable CCT	H	W	D
PATW0608LAJENBK	PATW0608LAJENTG	PATW0608LAJENBZ	12W	900	3000K/4000K/5000K	7-3/4"	6-1/4"	2-1/2"