

LIVING DISTRICT

Collection:Lennon

Installation manual for:


LD652D30 D31.5"H28.5" L4

Installation instructions:

- 1.Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 2.White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 3."E" wire from the fixture is attached to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 4.Secure mounting bracket to the junction box.
- 5.Insert screws (P2) in side of top unit the mounting bracket.
- 6.Put the lamp body to the right position.
- 7.Connect the top suction plate (P5) and the boom (P9),(P10),(P11) to the lamp body.
- 8.Put the canopy (P5) on the mounting bracket (P1) and use the Cap nut (P6) to screw tighten.
- 8.Put the plastic pad (P21) into the glass lamp shade (P20), then put it into the socket (P19), and lock it with the lamp ring (P22).
- 10.Install E26 light source,no include bulb.

The end!

PARTS LIST



"L" = Hot wire
 "N" = Neutral wire
 "E" = Ground wire

Part	Picture	Description	Qty	Check list
P1		L4" Mounting bracket	1	
P2		5/32-32 Screw	2	
P3		Hex nut	2	
P4		5/32-32 Screw	2	
P5		D4.72" Canopy cover	1	
P6		Cap nut	2	
P7		Power Cord 5.2' Black/Gold	1	
P8		Coupling	3	
P9		D0.63" * L6" ROD	1	
P10		D0.63" * L12" ROD	2	
P11		D0.63" * L16" ROD	1	
P12		D0.63" * L5.12" ROD	1	
P13		D2.76" Ball	2	
P14		D2.08" Ball cap	2	
P15		Cap nut	1	
P16		D0.46" * L15.7" Arm	4	
P17		D5.9" Receiver bowl	4	
P18		D1.65" Straight edge cover	4	
P19		E26 Socket	4	
P20		D9.8" * H8.9" Glass lampshade	4	
P21		Plastic pad	4	
P22		D2" Lamp ring	4	