


ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

| | |
|------------------------------------|---|
| ITEM NO.:DPC24 | NAME: Stirrups Pendant - 10" |
| MATERIAL TYPE:IRON, GLASS, LEATHER | FINISH: ANTIQUE BRASS, CREAM, SMOKE SEEDY |
| SOCKET TYPE: LED | SOCKET QTY: 1 |
| BULB WATTAGE: LED 12W | |
| VOLTAGE: 100V-120V | NET WEIGHT:11.4LBS |



PARTS INCLUDED:

| | | | |
|----------------------|----------|--------------------|---------|
| Mounting Plate(A) | Qty:1PC | Power Wire(L) | Qty:1PC |
| Canopy(B) | Qty:1PC | Fast Connector (P) | Qty:1PC |
| Collar (C) | Qty:1PC | | |
| Leather post (D) | Qty:1PC | | |
| Lamp Body (H) | Qty:1PC | | |
| Hexangular Screw (E) | Qty:8PCS | | |
| Rod (G1,G2,G3,G4) | Qty:4PCS | | |

HARDWARE INCLUDED:

| | |
|---------------------------|----------|
| Mounting Screw(J) | Qty:2PCS |
| Plastic Wire Connector(K) | Qty:3PCS |
| Green Ground Screw | Qty:1PC |

TO INSTALL YOU WILL NEED:

- 2 people recommended
- Phillips Screwdriver
- Allen Wrench

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.



TO ASSEMBLE:

- Shut off the main electrical supply from the main fuse box/ circuit breaker.
- Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
- Gently pull wiring down from ceiling junction box and allow to hang.
- Remove mounting plate(A) from the canopy(B) by unscrewing the collar(C).
- Screw the leather post(D) to the lamp body (H) until tight. Then Connect the leather post (D) with rods (G4). Repeat the same operation with rods (G3), (G2), and (G1). When you connect the rods, loosen the small hex screws (E) first, then tighten them with an Allen wrench (U) after all rods are connected. Ensure that all the hexagonal screws are tightened securely.
- Put the collar loop (C) and canopy (B) onto the rod (G1) in sequence, then thread the power wire (L) through the mounting plate (A). Secure the rod (G1) to the nipple of the mounting plate (A) until it is tight.
- PLEASE PAY SPECIAL ATTENTION TO THE FACT THAT YOU DO NOT NEED TO CONNECT THE WIRE TO THE DEVICE (M). IT IS USED FOR WIRE CONNECTIONS IN THE EUROPEAN MARKET.
- Carefully inspect the pendant's fixture wires.
Neutral fixture wire: White
Hot fixture wire: Black
Ground wire: Bare wire
- Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
- Attach the neutral fixture wire from the pendant to the neutral junction box wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.
- Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten each together with a wire nut and wrap the connection with electrical tape. **DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.**
- Please note that this product is suitable for 0-10V dimmer switch. Connect the purple wire (+) and the gray wire (-) to the dimmer switch as shown in below Figure 2. **BE SURE NO STRANDS ARE EXPOSED.**
- Connect the power wires(L) of the lamp together using the fast connector (P). Connect the black wire to the positive electrode and the white wire to the negative electrode of the fast connector (P).
- Gently tuck the wire connections(K) neatly into the ceiling junction box.
- Place the mounting plate(A) over the center of the ceiling junction box.
- Align holes in mounting plate(A) with holes in junction box and attach with two mounting screws(J). Secure screws with a Phillips head screwdriver.
- Push canopy up over the mounting plate until it is flush with the ceiling.
- Push collar(C) through hole in canopy(B) and thread onto nipple on the mounting plate(A). Secure by turning collar.




Fig.2

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.

For customer service questions call 1-800-338-2150

ARTERIOS