

ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

ITEM NO.: DMI35 NAME: Lotus Pendant

MATERIAL TYPE: Aluminum FINISH: Antique Brass

SOCKET TYPE: E-26 _____ SOCKET QTY: 3 PCS

BULB WATTAGE: 60 W

VOLTAGE: 220/240

ITEM NET WEIGHT: 25.13 LBS

PARTS INCLUDED:

Mounting Plate	Qty: 1 PC
----------------	-----------

Canopy	Qty: 1 PC
--------	-----------

3 Feet Chain	Qty 1 PC
--------------	----------

HARDWARE INCLUDED:

Mounting Screws	2
-----------------	---

Plastic Wire Connector	2
------------------------	---

Green Ground Screw	1
--------------------	---

TO INSTALL YOU WILL NEED:

- 2 people recommended • Phillips Screwdriver

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.



TO ASSEMBLE:

- Shut off the main electrical supply from the main fuse box/circuit breaker.
- Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
- Gently pull the wiring down from ceiling junction box and allow to hang.
- Remove mounting plate from the canopy by unscrewing the collar.
- Carefully inspect the pendant's fixture wires.
 - **Neutral fixture wire:** White
 - **Hot fixture wire:** Black
 - **Ground wire:** Green
- Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
- Attach the neutral fixture wire from the pendant to the neutral junction box wire (usually white). Fasten together with a wire nut and wrap the connection with electrical tape.
- Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten together with a wire nut and wrap the connection with electrical tape.
- DO NOT REVERSE THE HOT AND NEUTRAL
- CONNECTIONS OR SAFETY WILL BE COMPROMISED.
- Gently tuck the wire connections neatly into the ceiling junction box.
- Place the mounting plate over the center of the ceiling junction box.
- Align holes in mounting plate with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head screwdriver.
- Push canopy up over the mounting plate until it flushes with the ceiling.
- Push collar through hole in canopy and thread onto nipple on the mounting plate. Secure by turning collar clockwise until canopy is

CARE INSTRUCTIONS:

- Wipe with soft, dry cloth. To protect finish, avoid the use of harsh chemicals or abrasive cleaners.

For customer service questions call 1-800-338-2150

A R T E R I O R S