


ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

ITEM NO. :DLC55	NAME: LORYN CHANDELIER
MATERIAL TYPE:IRON, ALABASTER	FINISH:CHATTERED ANTIQUE BRASS, WHITE
SOCKET TYPE: E12	SOCKET QTY: 20
BULB WATTAGE: T 40W	
VOLTAGE: 100V-120V	ITEM NET WEIGHT:74.8LBS



PARTS INCLUDED:

Mounting Plate (A)	Qty:1PC
Canopy (B)	Qty:1PC
Collar (C)	Qty:1PC
Lamp Body (D)	Qty:1PC
Hex Screw (E)	Qty:8PCS
Alabaster Shade (F)	Qty:20PCS
Rod (G1,G2,G3,G4)	Qty:4PCS
Socket (H)	Qty:20PCS
Power Wire (L)	Qty:1PC

HARDWARE INCLUDED:

Mounting Screw (J)	Qty:2PCS	Allen Wrench (U)	Qty:1PC
Wire Cap (K)	Qty:3PCS	Metal Anchors (Q)	Qty:4PCS
Green Ground Screw	Qty:1PC	Strengthened Screw (R)	Qty:4PCS

TO INSTALL YOU WILL NEED:

- 2 people recommended
- Phillips Screwdriver
- Allen Wrench

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.



WARNING:

The ceiling must have at least the capacity of 5 times the weight of the fixture (74.8lbs.). For this fixture, a minimum ceiling capacity of 374lbs. is required. The manufacturer and distributor accept no liability for incorrect installation.

This fixture must be mounted to the ceiling independent of an outlet box. Your ceiling may require modification to allow the mounting plate to be secured to a structural member. This fixture MAY NOT be secured using any type of hollow ceiling anchor, such as a toggle bolt.

TO ASSEMBLE:

1. Shut off the main electrical supply from the main fuse box/ circuit breaker.
  2. Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
  3. Gently pull wiring down from ceiling junction box and allow to hang.
  4. Pass the power wire (L) through the rods (G4), (G3), (G2), and (G1). Screw the rod (G4) to the lamp body (D) until tight. Repeat the same operation with rods (G3), (G2), and (G1). When you connect the rods, loosen the small hex screws (E) in the side hole first, then tighten them with an Allen wrench (U) after all rods are connected. Ensure that all the hexagonal screws are tightened securely.
  5. Remove mounting plate from the canopy by unscrewing the collar.
  6. Place mounting plate (A) on the ceiling outlet and mark center points for four mounting holes of Mounting Plate (A) on the ceiling. Remove mounting plate (A).
  7. Drill small holes on the marked location; the holes should be big enough to accommodate with Metal anchors (Q). Push metal anchors (Q) into the holes.
  8. Pull the electrical cord of "J box "through the exit hole of the mounting plate(A).
  9. Carefully inspect the chandelier's fixture wires.  
Neutral fixture wire: It has very fine ridges molded into its plastic covering.  
Hot fixture wire: It has a smooth covering  
Ground wire: Bare wire
  10. Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
  11. Attach the neutral fixture wire from the chandelier to the neutral junction box wire. Fasten each together with a wire nut and wrap the connection with electrical tape.
  12. Attach the hot fixture wire from the chandelier to the hot junction box wire. Fasten each together with a wire nut and wrap the connection with electrical tape.
- DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
13. Gently tuck the wire cap(K) neatly into the ceiling junction box.
  14. Place the mounting plate(A) over the center of the ceiling junction box.
  16. Affix mounting plate (A) to ceiling outlet box. Insert Mounting Screws (J) into ceiling outlet and Strengthened Screw (R) to metal anchors (Q) to secure Mounting Plate (A) to the ceiling.
  17. Push collar (C) through hole in canopy(B) and thread onto nipple on the mounting plate(A). Secure by turning collar(C) clockwise until canopy(B) is flush with the ceiling.
  18. Insert 20 TYPE T 40W bulbs (or /CFL 12W OR /LED 10W, not included) into socket(H).  
DO NOT EXCEED THE SPECIFIED WATTAGE.
  19. Attach the alabaster shade (F) to the lamp body (D) by turning clockwise until tight.
  20. Restore power to junction box and test fixture.

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.

For customer service questions call 1-800-338-2150

ARTERIOS