ASSEMBLY INSTRUCTIONS

ARTERIORS

ITEM DESCRIPTION:

ITEM NO.: DMI37	**NAME:** Torsade Chandelier
MATERIAL TYPE: Glass+Iron	**FINISH:** Smoke
SOCKET TYPE: E12 Type B	**SOCKET QTY:** 5
BULB WATTAGE: 25W / 7W CFL / 5W LED	**VOLTAGE:** 125 V
ITEM NET WEIGHT: 30.4 LBS	



DIAGRAM PENDING FROM FACTORY

PARTS INCLUDED:

Mounting Plate	1	Canopy	1
Main Pipe (16")	1	Metal Disc (8 holes)	1
Pipes (one 3", one 6", two 12")	4	Glass Globe with Swivel Ball	4
Glass Globe without Swivel Ball	1	Coiled Arm	4
Ball Nut	4		

HARDWARE INCLUDED:

Mounting Screws	2	Allen Wrench	1
Plastic Wire Connector	2	Green Ground Screw	1

TO INSTALL YOU WILL NEED:

• 2 people recommended • Phillips screwdriver • Allen wrench (included)

TO ASSEMBLE:

1. Shut off power at the main fuse box or circuit breaker.
2. Carefully unpack all parts and hardware and lay them on a soft surface.
3. Thread the fixture cord through the 16" main pipe and screw the pipe onto the fixture body. Place the metal disc over it, lining up its 8 holes with the positions of the coiled arms.
4. Choose the pipes you need for your desired hanging height. Included are one 3", one 6" and two 12" pipes; the 3" pipe must always be used.
5. Thread the fixture cord through the pipes with the threaded ends toward the ceiling. Screw the pipes together, starting at the fixture body and working up to the canopy, then tighten the set screw on each pipe with the Allen wrench (included).
6. Gently pull the wires down from the junction box and let them hang.
7. Remove the mounting plate from the canopy by unscrewing the collar.
8. Strip about 3" of the cord's outer jacket without nicking the inner wires, then strip 3/4" of insulation from each wire (white = neutral, black = hot, green = ground).
9. Connect the fixture ground wire (green or bare) to the junction box ground wire (usually green or bare) with a wire connector and wrap with electrical tape. If there is no ground wire in the box, attach the fixture ground wire to the green ground screw on the mounting plate.
10. Connect the white (neutral) fixture wire to the white junction box wire with a wire connector and wrap with electrical tape.
11. Connect the black (hot) fixture wire to the black junction box wire with a wire connector and wrap with electrical tape. Make sure no wire strands are exposed.

DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.

12. Gently tuck all connections into the junction box.
13. Align the mounting plate with the junction box and attach it with the two mounting screws, using a Phillips screwdriver.
14. Slide the canopy up over the mounting plate until it is flush with the ceiling. Push the collar through the canopy, thread it onto the nipple of the mounting plate and turn it clockwise until the canopy is secure.
15. Insert five Type B bulbs, max 25W (or 7W CFL / 5W LED), not included, into the sockets. Do not exceed the maximum wattage.

GLASS GLOBE ASSEMBLY:

16. Screw the straight end of a coiled arm clockwise into the swivel ball on each of the four globes that have one.
17. On each outer socket, unscrew the metal bushing and slide the metal cap back.
18. Lift a globe with its coiled arm, insert the bent end of the arm into a hole in the metal disc and secure it with a ball nut, keeping the disc holes aligned with the globes.
19. Fit the opening of the globe inside the metal cap and tighten the cap screw just enough to hold the glass securely and centered.
20. Install the next globe on the opposite side so the fixture stays balanced, then install the remaining two arm globes the same way.
21. Install the fifth globe (without a swivel ball or arm) at the bottom position in the same way.
22. Restore power at the breaker and test the fixture.

IMPORTANT:

The glass is fragile. Handle it carefully and do not over-tighten, which can crack or break the glass.

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect the finish, avoid chemicals and household cleaners.

These instructions are provided for your safety. Read them carefully and completely before beginning installation. We strongly recommend that all hard-wired fixtures be installed by a licensed electrician.

Customer service: 1-800-338-2150