

Leo Switched

astro

General

Location:	Interior
Class:	cULus (Class 1)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Wall Mount - Horizontal Wall Mount - Vertical
Fitting Method:	Included Junction Box
Main Material:	Metal - Brass
Dimensions (mm):	H: 120 W: 45 D: 92
Dimensions (inch):	H: 4.72 W: 1.77 D: 3.62
Cut Out Hole (mm/inch):	H: 4.33" W: 1.38"
Recess Depth (mm/inch):	90mm/3.54"
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	2.64
Ada Compliant:	Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4
Ic Rating:	IC Rated

Lamp

Light Source:	High Power LED
Wattage:	4.3W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	134
Colour Temp (K):	2700
Cri (Ra):	90
Macadam Ellipse:	3-Step
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	L70 60000
Beam Angle (°):	18.1

Electrical

Switched:	Yes
Dimmable:	-
Dimming Method:	-
Supply Frequency (Hz):	50/60
Driver/Ballast Voltage (V):	100-240
Driver Average Lifetime (hrs):	60000
Efficacy (lm/W):	34.17

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



CODE: 1295009
FINISH: POLISHED CHROME



CODE: 1295010
FINISH: MATT NICKEL



CODE: 1295011
FINISH: BRONZE

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

