

Ascoli Swing Plug-In

astro

General

Location:	Interior
Class:	cULus (Class I)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Wall Mount
Fitting Method:	Hookup with Cord Set
Main Material:	Metal - Zinc
Dimensions (mm):	D: 286 Ø: 110
Dimensions (inch):	D: 11.26 Ø: 4.33
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	2500/98.43
Gross Weight (lb):	2.57
Ada Compliant:	Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4
Ic Rating:	-

Lamp

Light Source:	GU10
Wattage:	20W Max
Recommended Lamp:	6W Max LED GU10
6W Max LED GU10	No
Maximum Lamp Length (mm/inch):	57/2.24
Luminous Flux (lm):	Lamp Dependent
Colour Temp (K):	Lamp Dependent
Cri (Ra):	Lamp Dependent
Macadam Ellipse:	Lamp Dependent
Tilt Adjustable Angle (°):	90
Rotation Adjustable Angle (°):	180
Average Lifetime (hrs):	Lamp Dependent
Beam Angle (°):	Lamp Dependent

Electrical


Switched:	Yes
Dimmable:	No
Dimming Method:	-
Supply Frequency (Hz):	-
Driver/Ballast Voltage (V):	-
Driver Average Lifetime (hrs):	-
Efficacy (lm/W):	Lamp Dependent

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



CODE: 1286139
FINISH: MATT WHITE



CODE: 1286140
FINISH: MATT BLACK

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under u.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

