

# Renoir 680

astro

## General

Location:	Indoor
Class:	cULus (Class 1)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Wall Mount - Horizontal
Fitting Method:	3x2" Switch Box, 1/2" Stub Mount or 4x2" Handy Box
Main Material:	Metal - Aluminium
Dimensions (mm):	H: 60 W: 680 D: 245
Dimensions (inch):	H: 2.36 W: 26.77 D: 9.65
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	5.06
Ada Compliant:	Yes - if installed in compliance with ADA 307.2
Ic Rating:	-

## Lamp

Light Source:	Mid-Power LED
Wattage:	19.3W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (lm):	774
Colour Temp (K):	2700
Cri (Ra):	90
Macadam Ellipse:	3-Step
Tilt Adjustable Angle (°):	55
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	54000
Beam Angle (°):	103

## Electrical

Switched:	No
Dimmable:	Yes
Dimming Method:	0-10V
Supply Frequency (Hz):	50/60
Driver/Ballast Voltage (V):	110, 120-277
Driver Average Lifetime (hrs):	50000
Efficacy (lm/W):	40

## Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	-



Code: 1371023  
Finish: Bronze



Code: 1371035  
Finish: Matt Brushed Brass

To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.

Astro® is a registered trademark of astro lighting limited. Astro lighting's fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

Product Elevations

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

