

Silent Field Suspension orange/white

1012248A

SPECIFICATIONS



Design By

Carlotta de Bevilacqua
Laura Pessoni

Collection

Architectural



Specifications

Delivered lumens	1758lm
Light output ratio	73lm/W
Power consumption	24W
Led type	12X1.7W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire**
Input Voltage	120-277V
Driver	HATCH - 1 x XTC32-0700P-UNV-I

*Integrated light source **Reverse or forward phase (120v only)

Colors & Finishes

- Orange (Panel)
- White (Spotlights)


Materials

- Sound absorbing material
- PET, technopolymer
- Small spotlights (35 mm high, 25 cm diameter)

Features & Accessories

- A sound-absorbing surface supports 12 adjustable LED units
- Spotlights are connected to the surface by means of a spherical junction
- Possibility of 30° adjustment of the beam
- Sound properties are ensured by the geometry & by the varying density of the material used

Dimensions



Packaging

1 Box

1 x 43-13/16" x 8-3/8" x 44-3/16" / 25.57 lbs - 111 cm x 21 cm x 112 cm / 11.6 kg

Light distribution

Direct

Luminaire weight

15.87 lbs / 7.2 kg

Warranty

5 year limited warranty

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane