

Silent Field 2.0 suspension direct/indirect black

SPECIFICATIONS

1013038A



Design By

Carlotta de Bevilacqua
Laura Pessoni

Collection

Architectural



Specifications

Delivered lumens	5276lm
Light output ratio	70lm/W
Power consumption	75W
Led type	12X3W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 0-10V / Dimmable 2-Wire**
Input Voltage	120-277V
Driver	ENEDO - 1 x RCL040-0900A

*Integrated light source **2-wire dimming at 120VAC only

Colors & Finishes

Black (Panel)


Materials

- Sound absorbing material
- Platform in technopolymer

Features & Accessories

- Sound properties are ensured by the geometry & by the varying density of the material used
- Upper surface with low density to entrap soundwaves reflected from the ceiling
- Lower surface with different density to absorb different frequencies

Dimensions



Packaging

1 Box

1 x 43-13/16" x 8-3/8" x 44-3/16" / 25.57 lbs - 111 cm x 21 cm x 112 cm / 11.6 kg

Light distribution

Direct/Indirect

Luminaire weight

18.65 lbs / 8.46 kg

Warranty

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane