

# Silent Field 2.0 suspension direct/indirect white

## SPECIFICATIONS

1013028A



### Design By

Carlotta de Bevilacqua  
Laura Pessoni

### Collection

Architectural



### Specifications

Delivered lumens	5276lm
Light output ratio	70lm/W
Power consumption	75W
Led type	12X3W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 0-10V / Dimmable 2-Wire**
Input Voltage	120-277V
Driver	ENEDO - 1 x RCL040-0900A

### Colors & Finishes

☐ White (Panel)

### Materials


- Sound absorbing material
- Platform in technopolymer

\*Integrated light source \*\*2-wire dimming at 120VAC only

### Features & Accessories

- Sound properties are ensured by the geometry & by the varying density of the material used
- Upper surface with low density to entrap soundwaves reflected from the ceiling
- Lower surface with different density to absorb different frequencies

### Dimensions



### Packaging

1 Box

1 x 43-13/16" x 8-3/8" x 44-3/16" / 25.57 lbs - 111 cm x 21 cm x 112 cm / 11.6 kg

### Light distribution

Direct/Indirect

### Luminaire weight

18.65 lbs / 8.46 kg

### Warranty

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane