



- | | | | |
|-------------------------------|-----------------------|------------------------------|-------------------------------|
| (A) Mounting Screw (2x) | (B) Mounting Plate | (C) Canopy | (D) Flat screw_1 (2x) |
| (E) Lamp Fixture Body | (F) Flat screw_2 (3x) | (G) Lamp-holder Assembly | (H) External Bamboo Lampshade |
| (I) Interior Fabric Lampshade | (J) Snap Ring | (K) E26 LED Bulb (By others) | |

Installation instruction

Unpack and take out the fixture/accessories.

1. Turn off the power
2. Dismantle the mounting plate(B) from the canopy(C), then install it to J-Box with mounting screws(A).
3. Adjust the fixture's cable to the desired length.
4. Connect the fixture to a suitable ground in accordance with local electrical codes.
5. Connect the White wire to the neutral power line wire with a wire nut.
6. Connect the Black wire to the hot power line wire with a wire nut.
7. Neatly place all wires and wire nut connections inside the J-box.
8. Install the canopy(C) to ceiling with 2PCS flat screws_1(D).
9. Assemble the lamp-holder assembly(G) of the lamp fixture body(E) to the top of external bamboo lampshade(H) with flat screws_2(F), and then lock the interior fabric lampshade(I) to the lamp-holder assembly(G) with snap ring(J).
10. Screw E26 LED bulb(K) into the the lamp-holder.
11. After finish the installation, then turn on the power.