

# U-Light

Timo Ripatti



Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy


WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version



wall or ceiling lamp recessed version




acoustic performance

## UP UL 1 090 3 7/8" recessed UP UL 2 090 9 7/8" recessed



3 7/8" lb 5.95 ft³ 4.44  
9 7/8" lb 6.83 ft³ 4.44

U-LIGHT / 3 7/8" or 9 7/8" recessed ceiling lamp / DRIVER NOT INCLUDED


Type	Article	Colours	Version	Source
UP	UL 1 090 LED (3 7/8")	AN anthracite grey	IN recessed canopy	LED 54W - diffused beam <b>3000K*, 2700K</b> 24VDC  other CCT options available upon request
	UL 2 090 LED (9 7/8")	RU rust brown		



recessed canopy



available heights



3 7/8" height

9 7/8" height



DRY LOCATION CRI90



LED

~5158 lm\* 95 lm/W\* 24Vdc

hole Ø 13/4" / min depth 3 7/8"

ADA COMPATIBLE only for UL1090LED

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code UP UL1090LED RU IN  
Casambi compatible.



KITFAPLUL090IAV sound absorbing option ivory.  
For more information see page 156

## Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,01	0,11	0,32	0,68	0,63	0,63	0,58	0,42	0,54

CUSTOMER \_\_\_\_\_

NOTES \_\_\_\_\_

UP UL \_ 090 LED \_ \_ IN

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.