

U-Light

Timo Ripatti



Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy

WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version




wall or ceiling lamp recessed version




acoustic performance

UP UL 1160 3 7/8" recessed UP UL 2160 9 7/8" recessed


3 7/8" lb 11.02 ft³ 9.88
9 7/8" lb 11.9 ft³ 9.88




recessed canopy



min depth
3 7/8"




hole Ø 2 1/2"



available heights



3 7/8"
height



9 7/8"
height

U-LIGHT / 3 7/8" or 9 7/8" recessed ceiling lamp / DRIVER NOT INCLUDED

Type	Article	Colours	Version	Source
UP	UL 1160 LED (3 7/8")	AN anthracite grey	IN recessed canopy	LED 102W - diffused beam 3000K*, 2700K 24VDC other CCT options available upon request
	UL 2160 LED (9 7/8")	RU rust brown		



DRY LOCATION

CRI90



LED ~9025 lm* 88 lm/W* 24Vdc

hole Ø 1 3/4" / min depth 3 7/8"

ADA COMPATIBLE only for UL1160LED

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code UP UL1160LED RU IN

Casambi compatible.



KITFAPLUL000IAV sound absorbing option ivory.

Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,05	0,29	0,93	1,48	1,60	1,52	1,45	1,04	1,34

UP UL _ 160 LED _ _ IN

CUSTOMER _____

NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.