

U-Light

Timo Ripatti



Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

sound absorbing product

COLOURS



anthracite grey



canopy



rust brown




canopy

WALL AND CEILING LAMP VERSION




wall or ceiling details


wall or ceiling lamp
canopy version

wall or ceiling lamp
recessed version



acoustic performance

UP UL 1 090 3 7/8" canopy UP UL 2 090 9 7/8" canopy


3 7/8" lb 12.78 ft³ 4.51
9 7/8" lb 13.88 ft³ 4.51



standard canopy



available heights


3 7/8"
height

9 7/8"
height

U-LIGHT / 3 7/8" or 9 7/8" ceiling lamp with canopy / DRIVER INCLUDED /

Type	Article	Colours	Version	Source
UP	UL 1 090 LED (3 7/8")	AN anthracite grey	XX standard canopy	LED 63W - diffused beam 3000K*, 2700K other CCT options available upon request
	UL 2 090 LED (9 7/8")	RU rust brown		



DRY LOCATION

CRI90



LED

~5158 lm* 82 lm/W* 100-305VAC

ADA COMPATIBLE only for UL1090LED

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code UP UL2090LED AN XX

Casambi compatible.



KITFAPLULA090AV sound absorbing option ivory.
For more information see page 156

Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,01	0,11	0,32	0,68	0,63	0,63	0,58	0,42	0,54

UP UL _ 090 LED _ _ XX

CUSTOMER

NOTES

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.