

U-Light

Timo Ripatti



Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

sound absorbing product

COLOURS



anthracite grey



canopy



rust brown




canopy

WALL AND CEILING LAMP VERSION



wall or ceiling details


wall or ceiling lamp
canopy version

wall or ceiling lamp
recessed version


acoustic performance

US ULA 180 canopy US ULA 180 recessed

canopy lb 23,5 ft³ 11,65
recessed lb 11,9 ft³ 10,95

Installazione downlight o uplight.
Downlight or uplight mounting.

U-LIGHT / suspension with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
US	ULA 180 LED	AN anthracite grey RU rust brown	XX standard canopy	LED 153W - diffused beam 3000K*, 2700K other CCT options available upon request



DRY LOCATION

CRI90



LED

~10315 lm* 67 lm/W* 100-305VAc

Casambi compatible.

U-LIGHT / recessed suspension lamp / DRIVER NOT INCLUDED

Type	Article	Colours	Version	Source
US	ULA 180 LED	AN anthracite grey RU rust brown	IN recessed canopy	LED 123W - diffused beam 3000K*, 2700K 24VDC other CCT options available upon request



DRY LOCATION

CRI90



LED

~10315 lm* 84 lm/W* 24Vdc

hole Ø 1 3/4" / min depth 3 7/8"

example composition code US ULA180LED AN IN

Casambi compatible.



KITFASPULA000AV sound absorbing option ivory.
For more information see page 156

Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,11	0,65	2,06	3,63	3,63	3,64	3,45	2,45	3,11

US ULA 180 LED _ _ _ _

CUSTOMER

NOTES

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.