

BUSTER+PUNCH

LONDON

[product.]

KITCHEN FAUCET / MIXER

[action. **SINGLE LEVER MIXER.**]

[water. **WARM + COLD.**]

[knurl. **CROSS.**]

[range. **KITCHEN.**]

A kitchen faucet with single lever mixer. This faucet has been cast, sand-blasted and machined from solid metal in Italy. It features our signature cross-knurl pattern and is refined by hand. Available in three metal finishes: steel, gun metal and welders black.



[type. **FAUCET / MIXER.**]

[info. **MEASUREMENTS.**]



[info. **SPECIFICATIONS.**]

A kitchen faucet with a single lever action that mixes water from the hot and cold pipes in your kitchen.

Maximum thickness of mounting surface 40mm, with supplied fixings.

Minimum recommended water pressure: 7.25 PSI (0.5 BAR).

Maximum recommended water pressure: 72 PSI (5 BAR).

Recommended maximum hot water temperature: 70 °C (158°F).

Recommended temperature range: 5 – 60 °C (41 – 140 °F).

Note: exceeding these temperatures or water pressures can result in damage to the tap. A pressure reducing valve may be required to be fitted in high water pressure situations.

[info. **FINISH & SKU NUMBERS.**]

[finish.]

[US.]

● Steel

NKT-071668

● Gun Metal

NKT-351671

● Welders Black

NKT-591670

[info. **CARE INSTRUCTIONS.**]

Wipe with damp cloth with no loose hairs, avoid using any chemicals. All finishes are prone to aging.

[info. **INCLUDED.**]

1 x Single Lever Faucet Mixer

1 x Kitchen Mixer Faucet

2 x Flexible connector hoses

1 x Tap Base and set of washers

1 x Threaded bar and nut

1 x Supporting tap brace (for surfaces with thickness < 5mm)

[info. **INSTALLATION TOOLS REQUIRED.**]

1 x Adjustable spanner

[please. **NOTE.**]

All Buster + Punch mixer taps conform to standard EN817. In some cases, local housing regulations may require mixer taps to be of a higher minimum water pressure standard. In this instance we would recommend consulting with a certified plumber about installing a pressure regulator or similar device.

Mixer taps are tested to work with a max. pressure of 10 bar (1000 kPa) and recommended working pressure range is 1.0 – 5.0 bar (100 kPa – 500 kPa).