

Project:

Type:

Quantity:

Note:

SKU#: NAN - 25V - - - 30K -

Description

Nano vanity lights represent extraordinary value. The super-efficient LED light source inside the minimal geometric form illuminates the white frosted acrylic diffuser.

Features

- Stamped steel construction
- Frosted acrylic extruded diffuser
- Driver located in fixture's backplate
- Damp location rated
- JA8-2016 listed



QUICK SHIP | AVAILABLE IN 2 WEEKS
Deep Backplate Standard Finish
12T Triac Option Only



Specifications

- Color Rendering Index: 90CRI
- LED Color Temperature: 3000K (standard)
- Fixture Wattage: 22W
- Input Voltage: 120VAC 50/60Hz
- Delivered Lumens: 1041 Lm (measured at 3000K)
- Fixture Weight: 4.4lb (2kg)
- Backplate: S4 - 4.6" x 4.6" x .5" (Standard)
- Dimming: TRIAC dimmable
- For recommended dimmers, see <http://www.blackjacklighting.com>

Options

- Upgradeable to 120-277V input driver with Universal Dimming
- Available in 2700K, 3000K, 3500K, and 4000K Color Temperatures
- Standard Finishes: PC - Polished Chrome, SN - Satin Nickel
- Special Order Powder Coat Finishes: BL - Matte Black, BZ - Bronze, SG - Satin Gold, or Satin Silver
- Optional Deep Backplate (DB) - 4.6" x 4.6" x 1.3"

Dimensions



NAN-25V-PC-12T-30K-DB

ORDERING GUIDE

Family	Size	Finish	Volts/Dimming	Color Temp.	Backplate
NAN	25V			30K	
NAN Nano	25V 25" Vanity	Standard PC Polished Chrome SN Satin Nickel Special Order BL Matte Black BZ Bronze SG Satin Gold SS Satin Silver	Standard 12T 120VAC TRIAC Dimming Only (All Backplates) Special Order 27U 120-277VAC Universal Dimming (Deep Backplate Only) 27Z 120-277VAC (0-10V Dimming Only) (Shallow S4 Backplate Only)	30K 3000K (Default) 27K 2700K 35K 3500K 40K 4000K	Standard S4 4.6" Shallow Backplate (Standard) (Driver located inside junction box) Special Order DB Deep Backplate (Driver located in backplate)


Example: NAN-25V-PC-12T-30K-S4

Finish  PC SN BL BZ SG SS	Standard Finishes   PC Polished Chrome SN Satin Nickel	Special Order Powder Coat Finishes     BL Black BZ Bronze SG Satin Gold SS Satin Silver
--	--	---


Volts/Dimming  12T 27U 27Z	<p>12T: Input: 120V , Dimming: TRIAC (Standard)</p> <p>27U: Input: 120-277V , Dimming: TRIAC/ ELV/ 0-10V (Deep Backplate Only) (Special Order)</p> <p>27Z: Input: 120-277V , Dimming: 0-10V (Shallow S4 Backplate Only) (Special Order)</p>
--	--

Color Temperature  27K 30K 35K 40K	27K 2700K 30K 3000K (Default) 35K 3500K 40K 4000K
---	--






Front Plate




DB - Deep Backplate (Optional)
4.6" H, 4.6" W, 1.3" D
Driver located inside Backplate





Front Plate



S4 - Shallow Backplate (Standard)
4.6" H, 4.6" W, .5" D
Driver located inside J-Box