

3" WHITE GLASS GLOBE SUSPENDED SMALL PENDANT




SPECIFICATIONS

Finish	Matte Black, White, or Polished Chrome
LED Color Temperature	3000K (standard) 2700K, 3500K, or 4000K also available
Wattage	2 Watts / 146 Lumens 3 Watts / 234 Lumens
Driver Location	Integral in canopy, remote, or above canopy (depending on canopy selected)
Dimming	Universal (TRIAC, ELV, 0-10V)
Color Rendering Index	90CRI
Input Voltage	120VAC - 50/60Hz
Cable Length	8' (for longer lengths, consult factory)

CUSTOM OPTIONS

See page 2 for socket finish and cord color options.




ORDERING GUIDE

PRODUCT CODE								OPTIONS	
CATEGORY	SERIES	DIFFUSER	SIZE	SOCKET COLOR	CCT	WATTAGE	MOUNTING	CABLE LENGTH	
SP	GGG	WH	03						
SP Small Pendant	GGG Small White Glass Globe	WH White	03 3" Diameter	Standard BL - Matte Black WH - White PC - Polished Chrome Special Order BZ - Bronze SG - Satin Gold SS - Satin Silver	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K (30K Standard)	2W 2 Watts / 146 Lm 3W 3 Watts / 234 Lm	SP2 - 2.5" Canopy SP5 - 5" Canopy MPC - Multi-Port Canopy JTA - JackTrack	Indicate Cable Length in Inches - leave blank for default 096 = 96" (default) 300 = 300" (max.)	

Example Part Number: SP-GGS-WH-03-BL-30K-3W-SP5-96-BL

Socket Color




Wattage (Lumens measured at 3000K)

- 2W** = 2 Watts / 86 Lumens, **recommended for Multi-Port applications** (Multi-Port system and JackTrack adapter).
- 3W** = 3 Watts / 204 Lumens, **recommended for single pendant applications** (5" Canopy and 2.5" Fascia Canopy).

Mounting
























- SP5** = 5" round canopy with integrated driver (included), attaches to rear of canopy and sits inside ceiling mounted junction box  
*Cable with modular connector attaches to canopy w/ integrated universal driver (120-277V / TRIAC, ELV, 0-10V dimming)*
- SP2** = 2.5" thin profile round canopy that attaches flush to a rigid ceiling (driver sold separately)  
*Cable with modular connector (and optional wire harness) attaches to a remote driver*
- MPC** = Multi-port connector attaches to any of BlackJack's Multi-Port canopies (canopy and driver sold separately)  
*Cable with modular connector attaches to a driver inside a Multi-Port canopy (driver may be remote)*  
MPC options include:  
Solo Systems, Duo Systems, Quatro Systems, and JackTrack Systems  
MPC, MPR, MS, MQ, MD canopies
- JTA** = Adapter connects the pendant in any position along the JackTrack system (track and driver sold separately)  
*Cable is cut to length and inserted in a connector at the bottom of the JackTrack adapter*



Cable Length

- 096** = 96" (Default Length).
- XXX** = Custom Length (300" = maximum length)
- For Custom Lengths, please indicate length in inches.

For more information on Solo Systems, Duo Systems, Quatro Systems, JackTrack Systems, or Multi-Port Canopies, see [blackjack.com](http://blackjack.com).

Pendant Mounting	Canopy	Dimensions	End / Side View	Finish Options
SP5	<b>5" Canopy</b> Canopy and driver included with pendant	 5" dia. (12.7 cm)	 .8" (2 cm) (Integrated Driver)	BL Matte Black PC Pol. Chrome WH White SG Satin Gold BZ Bronze SS Satin Silver
SP2	<b>2.5" Fascia Canopy</b> Canopy included with pendant. Driver sold separately.	 2.5" dia. (6.4 cm)	 .4" (1.3 cm) (Remote Driver required)	BL Matte Black PC Pol. Chrome WH White SG Satin Gold BZ Bronze SS Satin Silver
MPC MPS MQ	<b>24" Multi-Port Square - 9 Port</b> C-MPS-2409-# MQ-2409-#  <b>24" Multi-Port Square - 25 Port</b> C-MPS-2425-# MQ-2425-#	 8" OC (20.3 cm) 23.9" (60.7 cm) 9 Port   4.8" OC (12.2 cm) 23.9" (60.7 cm) 25 Port	 21.5" 54.6 cm 2.5" (6 cm) (Integrated or Remote Driver)	BL Matte Black PC Pol. Chrome WH White SG Satin Gold BZ Bronze SS Satin Silver
MPC MPT MD	<b>38" Multi-Port Rectangle - 10 Port</b> C-MPT-3810-# MD-3810-#  <b>38" Multi-Port Rectangle - 18 Port</b> C-MPT-3818-# MD-3818-#	 7.5" OC (19 cm) 37.7" (97.8 cm) 3" OC (7.6 cm) 10 Port   4.1" OC (10.4 cm) 37.7" (97.8 cm) 2.5" OC (6.4 cm) 18 Port	 4.7" 11.9 cm 2.5" (6 cm) 6" 15.2 cm (Integrated or Remote Driver)	BL Matte Black PC Pol. Chrome WH White SG Satin Gold BZ Bronze SS Satin Silver
MPC MPL	<b>22" Multi-Port Linear - 5 Port</b> C-MPL-2205-# MS-2205-#  <b>48" Multi-Port Linear - 11 Port</b> C-MPL-4811-# MS-4811-#	 4.4" OC (11.2 cm) 21.8" (56 cm) 2.8" (7 cm) 5 Port   4.4" OC (11.2 cm) 48" (123 cm) 2.8" (7 cm) 11 Port	 2.8" (7 cm) 1.4" (4 cm) (Integrated or Remote Driver)	BL Matte Black PC Pol. Chrome WH White SG Satin Gold BZ Bronze SS Satin Silver
MPC MPR	<b>10" Round - 3 Port</b> C-MPR-1003-#  <b>10" Round - 9 Port</b> C-MPR-1009-#	 7.4" OC (18.8 cm) 11" dia. (27.9 cm) 3 Port   2.9" OC (7.4 cm) 11" dia. (27.9 cm) 9 Port	 10" dia. (25.4 cm) 2.1" (5.3 cm) (Integrated Driver)	BL Matte Black PC Pol. Chrome WH White SG Satin Gold BZ Bronze SS Satin Silver
MPC MPR	<b>20" Round - 3 Port</b> C-MPR-2003-#  <b>20" Round - 12 Port</b> C-MPR-2012-#	 14.5" OC (36.8 cm) 20" dia. (50.8 cm) 3 Port   6.4" OC (16.3 cm) 20" dia. (50.8 cm) 12 Port	 18" dia. 45.7 cm 2.5" (6 cm) (Integrated Driver)	BL Matte Black PC Pol. Chrome WH White SG Satin Gold BZ Bronze SS Satin Silver
JTA	<b>24" JackTrack</b>  <b>48" JackTrack</b>  <b>94" JackTrack</b>	 23" (58.4 cm) 1.75" (4.5 cm)   47" (119.4 cm) 1.75" (4.5 cm)   94" (238.8 cm) 1.75" (4.5 cm)	 1.38" (3.5 cm) 1.75" (4.5 cm) (Integrated or Remote Driver)	BL Matte Black WH White

For more information on Solo Systems, Duo Systems, Quatro Systems, JackTrack Systems, or Multi-Port Canopies, see [blackjack.com](http://blackjack.com).

System	Pendant Mounting	Configuration Examples		Finish Options
<b>Quatro</b>  4S (4' 2x2 / 9 Port) MQ-2409-XX-4S-X-XXX		<b>Square Configurations</b>  	<b>6S (6' 3x3 / 25 Port)</b> MQ-2425-XX-6S-X-XXX	BL Matte Black PC Pol. Chrome BZ Bronze SG Satin Gold SS Satin Silver
		<b>Linear Configurations</b>  	<b>6L (6' x2' / 25 Port)</b> MQ-2425-XX-6L-X-XXX	
<b>Duo</b>  6L (6'4"x6" / 10 Port) MD-3810-XX-6L-X-XXX  9L (9'6"x6" / 18 Port) MD-3818-XX-9L-X-XXX		<b>Linear Configurations</b>  	BL Matte Black PC Pol. Chrome BZ Bronze SG Satin Gold SS Satin Silver	
<b>Solo</b>		<b>Solo 48" Linear Configuration</b>  	<b>Solo (L) Configuration</b>  	BL Matte Black PC Pol. Chrome BZ Bronze SG Satin Gold SS Satin Silver
		<b>Solo 22" Grid Configuration</b>  	<b>Solo 48" Grid Configuration</b>  	