

Carlow Linear Chandelier

CC1586 | 1.1

GENERATION LIGHTING CHANDELIER

GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes.


This product is safety listed for damp locations.

Incandescent version may be dimmed with a standard incandescent dimmer. LED version may be dimmed with a LED dimmer. Consult lamp manufacturer for additional information.

This instruction shows a typical installation.


CAUTION - RISK OF FIRE
 This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
Use minimum 90°C supply conductors.

SAVE THESE INSTRUCTIONS!



GENERATION LIGHTING
 7400 Linder Ave., Skokie, IL 60077
 T 847.410.4400 | F 847.410.4500
www.generationlighting.com

Install the Fixture



- 1** Temporarily install the mounting to the junction box and mark the anchor locations through the holes on the mounting plate.
- 2** Remove the mounting plate, drill appropriate sized holes at the marked locations and install the anchors.
- 3** Secure the mounting plate to the junction box and screw the anchor screws into the anchors.
- 4** Feed the fixture wires through the stems, then screw the stems onto the socket assembly.
- 5** Feed the fixture wires through the plate, upper frame, washers, and fixture loops, then secure them to the stems by screwing on the fixture loops.
- 6** Place the center frame on top of the lower frame, then lower the upper frame onto the center frame and secure them together using the frame washers and screws as shown. **NOTE: This step will require the help of another person.**
- 7** Install the candle tubes by sliding them over the sockets.
- 8** Screw the lamps into the sockets. Refer to the label on the lamp socket for Max Wattage Information.
- 9** Determine the wanted height of the fixture and remove a portion of the chain from the bottom by opening a link with pliers.
- 10** Install the large quick link to bottom end of the chain, then secure the large quick link onto the fixture loop.
- 11** Install the small quick link onto the remaining end of the chain, then secure the small quick link onto the canopy loop.
- 12** Weave the cord through the chains, canopy loops, and canopy, and out of the junction box. Trim the cord leaving enough to make electrical connections.
- 13** Connect the fixture to a suitable ground in accordance to local electrical codes.
- 14** Connect the white fixture wire (square and/or rigid) to the neutral power line wire with a wire nut.
- 15** Connect the black fixture wire (round and/or smooth) to the hot power line wire with a wire nut.
- 16** Neatly place all the wires into the junction box, place the canopy onto the mounting plate, and secure it in place by using the fixture screws.