


Indirect panel

Imagine being able to create the perfect mood when dimming your lights. This is now possible with our Dim to Warm concept, generating a warm, exquisite glow to set the tone for your evening.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
IND4-DW	4"	9 W	500 lm	975 lm	80	3000 K - 2200 K	120 V
IND6-DW	6"	12 W	750 lm	1500 lm	80	3000 K - 2200 K	120 V

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained
 Over 50,000 hours of service life
 Dim-to-warm technology, dims from 3000 K to 2200 K to mimic incandescent light
 Smooth 360° wide spread
 Minimal heat emission
 Dome reflector
 110° beam spread
 Indirect lighting design with glare reduction

Aluminum construction
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 Suitable for damp locations
 Refer to website for dimmer compatibility
 5-year warranty

Finish

○ **WH** White

Accessories

RFP-UNI

Universal rough-in plate

RFP-46

Rough-in plate for 4" and 6" models

Order example

IND4-DW-WH

Indirect 4" recessed fixture with variable CCT through dimming between 3000 K and 2200 K in a white finish


Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.





IND4-DW

Ø4 3/8"



IND6-DW

Ø6 1/4"



5-1/16" x 3" x 1-5/16"