

# WAC LIGHTING

## Cloak

### Pendant 4CCT

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-58506 6"	2700K	BK Black	15W	1259	884
	3000K	WT White			
	3500K				
	4000K				

Example: **PD-58506-40-WT**

For custom requests please contact [customs@waclighting.com](mailto:customs@waclighting.com)

#### DESCRIPTION

Tubular. An opaque tube surrounds an acrylic shade, directing illumination in a downward design.

#### FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Driver included
- 5 Year warranty

#### SPECIFICATIONS


Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 10-100% , TRIAC: 10-100%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware



#### FINISHES:



#### LINE DRAWING



PD-58506

# WAC LIGHTING

## Cloak

### Pendant 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-58509 9"	2700K	BK Black	21W	1934	1505
	3000K	WT White			
	3500K				
	4000K				

Example: **PD-58509-40-WT**

For custom requests please contact [customs@waclighting.com](mailto:customs@waclighting.com)

#### DESCRIPTION

Tubular. An opaque tube surrounds an acrylic shade, directing illumination in a downward design.

#### FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Driver included
- 5 Year warranty

#### SPECIFICATIONS


Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 10-100% , TRIAC: 10-100%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware



#### FINISHES:



#### LINE DRAWING



PD-58509