

Tik

bollard light



Table of contents

1. Product Overview	Page 2
2. Finishes & Materials	Page 2
3. Light Source & Dimming	Page 2
4. Installation	Page 3
5. Photometric Data & Technical Information	Page 3
6. Ordering Codes	Page 4
7. Certifications & Standards	Page 5
8. Maintenance & Cleaning	Page 5

Versions



TIK_4096X
Page 4



TIK_4097X
Page 4

Tik

bollard light

1. Product Overview

Metallic outdoor bollard light with a PMMA lens diffuser (60° beam angle) and integrated LED, providing direct light.

The cylindrical tube encloses the light source and it is non-adjustable.

Model TIK_4096X directs the light downward.

Model TIK_4097X directs the light upward.

Built-in driver for direct connection. Surface-mounted on a solid base.

A double-layer coating ensures high resistance to corrosion and maritime environmental conditions.



2. Finishes & Materials



88 Grey Stone

89 Pale Green

96 Anthracite

3. Light Source & Dimming

Lamping

LED 6.2W (2700K / Ang. 60° / >90 CRI / 350mA) 120V / Typ 725 lumens

Optic lens: (PMMA) lens diffuser 60°.

*Integrated LED module (included).

Dimming options:

Standard: TRIAC

Tik

bollard light

4. Installation

Built-in driver for direct connection

Surface-mounted on a solid base (concrete or similar).
Not suitable for installation on soil or grass.

60° beam angle


Acrylic optic. It provides diffused uniform illumination and it is visible as a decorative light line when seen from the side.



5. Photometric Data & Technical Information

Photometric data corresponds to the output of each individual lamp.
Access to photometric files in download area.

2D / 3D / BIM Files available. Access to files in download area here.



Tik

bollard light

6. Ordering Codes

Lamping 4096X
 LED 6.2W (2700K / Ang. 60° / >90 CRI / 350mA)
 120V / Typ 725 lumens
 Optic lens: (PMMA) lens diffuser 60°
 DIM: TRIAC

Finishes:
 88 Grey Stone
 89 Pale Green
 96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4096X 	Bollard light. Hard wired (no plug). Surface mounted on a solid base.	Outdoor	Grey Stone	TIK_4096X_88W
		Outdoor	Pale Green	TIK_4096X_89W
		Outdoor	Anthracite	TIK_4096X_96W

Lamping 4097X
 LED 6.2W (2700K / Ang. 60° / >90 CRI / 350mA)
 120V / Typ 725 lumens
 Optic lens: (PMMA) lens diffuser 60°
 DIM: TRIAC

Finishes:
 88 Grey Stone
 89 Pale Green
 96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4097X 	Bollard light. Hard wired (no plug). Surface mounted on a solid base.	Outdoor	Grey Stone	TIK_4097X_88W
		Outdoor	Pale Green	TIK_4097X_89W
		Outdoor	Anthracite	TIK_4097X_96W

7. Certifications & Standards



Warranty: 1 year
100% made in Spain

Estiluz products are guaranteed against manufacturing defect for one year from date of delivery. Estiluz products with integral LED modules and drivers are guaranteed against manufacturing defects for five years from date of delivery. This guarantee is limited to replacement of defective material and does not include any labor, expenses or damages contingent or incidental thereto. This warranty does not apply to products damaged due to accident, tampering, misuse or abuse.

8. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.