


LUCK

T-2443 USA / T-2443F USA 493024432

Metallic pendant with direct and indirect light. Transparent glass ball shade, diagonal opening on the bottom. Adjustable height.



UL 1598 ELECTRICAL INSTRUCTIONS FOR FLUSH MOUNTS, WALL SCONCES AND PENDANTS


SAVE THESE INSTRUCTIONS. MIN 90C SUPPLY CONDUCTORS. CAUTION-RISK OF FIRE. USE STATED WATT OR SMALLER. CAUTION-RISK OF SHOCK. DISCONNECT POWER BEFORE SERVICING. TO REDUCE THE RISK OF A BURN DURING RELAMPING, ALLOW THE BULB TO COOL DOWN. SUITABLE FOR DRY LOCATIONS ONLY. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARD INVOLVED.

WARNING: ALL WIRES AND WIRE NUTS USED IN THE INSTALLATION MUST BE RATED 195F (90°C). FOR INDOOR USE ONLY. THESE PRODUCT MUST BE INSTALLED BY A QUALIFIED ELECTRICIAN.

Assembly instructions


1- Remove the lateral screw (A) to separate the canopy from the mounting bracket. Figure 1.

1



2- Insert the electrical wire through the finished knob (B). Insert the electrical wire through the cable strap as shown (C). Connect the electrical wires. Affix the mounting bracket to the ceiling or to the electrical junction box. Figure 2.


2



Instrucciones /Assembly instructions

3

3- Unscrew and remove the ring [E] from the socket. Figure 3.



4- Set the glass shade over the socket with the concave side facing down. Screw the metal ring back in place [E]. Insert the bulb. Figure 4.

4

