



Measurements

Surface

L

A: 232/9.13" A1: 180/7.09" F: ø1320/52"

S

A: 232/9.13" A1: 180/7.09" F: ø1060/41.7"




Recessed

L

A: 180/7.09" A1R: 120/4.72"

S

A: 180/7.09" A1R: 120/4.72"



Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	20
Suitable for seaside areas	No
Structure material	Aluminium
Blade material (fan blades)	Plywood
Structure finish	Matt Black
RAL/Pantone structure	RAL 9005
Blade finish	Walnut
Blade finish 2	Matt Black
Motor type	DC
Fan power (W)	4-6-10-17-24-35
RPM	85-109-134-159-180-203
Airflow (m³/min)	72-94-116-140-156-174
Airflow (CFM)	2566-3316-4109-4935-5521-6146
Sound intensity (dBA)	37-37-38-40-43-47
Number of blades	3
Maximum tilt (°)	12
Type of control included	Remote control with timer
Fan programming hours	1-4-8h
Rod diameter	26
Optional rod model	Universal 26mm



Installation instructions

Related accessories



White wall controller for DC fan with dimmable light

Reference	33987
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



Black wall controller for DC fan with dimmable light

Reference	33988
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



Wall controller white rf applique 6 speeds

Reference	34306
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



Wall controller black rf applique 6 speeds

Reference	34307
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



TAKI Light kit black SWT 20W dimmable	
Reference	3L043
Voltage (V)	220V-240V
Hertz	50/60Hz
IP	20
Structure material	Aluminium



White remote control	
Reference	34303
IP	20
Structure material	ABS

