

IK03 IP44




Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	44
IK	03
Suitable for seaside areas	Yes
Structure material	Steel
Blade material (fan blades)	ABS
Structure finish	Matt White
RAL/Pantone structure	RAL 9016
Blade finish	Matt White
Motor type	DC
Fan power (W)	4-6-9-14-20-27
RPM	86-121-146-175-198-222
Airflow (m³/min)	67-83-108-121-150-174
Airflow (CFM)	2372-2948-3823-4479-5305-6142
Sound intensity (dBA)	38-39-41-46-49-52
Number of blades	3
Maximum tilt (°)	12
Type of control included	Remote control with timer
Fan programming hours	1-4-8h
Rod diameter	26
Optional rod model	Universal 26mm

Measurements

Surface

M

A: 245/9.65" A1: 221/8.7" F: ø1250/49.2"



Installation instructions



Related accessories



Wall controller white rf applique 6 speeds

Reference	34306
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



Wall controller black rf applique 6 speeds

Reference	34307
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



White wall controller for DC fan with dimmable light

Reference	33987
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



Black wall controller for DC fan with dimmable light	
Reference	33988
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass

