




Measurements


Surface

L
A: 240/9.45" A1: 220/8.66" F: ø1500/59.1"
M
A: 240/9.45" A1: 220/8.66" F: ø1250/49.2"
S
A: 240/9.45" A1: 220/8.66" F: ø925/36.4"



Recessed

L
A: 180/7.09" A1R: 160/6.3"
M
A: 180/7.09" A1R: 160/6.3"
S
A: 180/7.09" A1R: 160/6.3"



Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	20
Suitable for seaside areas	No
Structure material	Steel
Blade material (fan blades)	Pine Wood
Structure finish	Matt Black
RAL/Pantone structure	RAL 9005
Blade finish	Dark Walnut
Motor type	DC
Fan power (W)	12-13-16-20-25-35
RPM	108-115-123-134-142-156
Airflow (m³/min)	92-107-122-136-149-162
Airflow (CFM)	3247-3781-4309-4774-5263-5698
Sound intensity (dBA)	29-29-31-34-38-40
Number of blades	3
Maximum tilt (°)	12
Type of control included	Remote control with timer
Fan programming hours	1-4-8h
Rod diameter	26
Optional rod model	Universal 26mm



Installation instructions

Related accessories



Wall controller white rf applique 6 speeds

Reference	34306
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



Wall controller black rf applique 6 speeds

Reference	34307
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



White wall controller for DC fan with dimmable light

Reference	33987
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



Black wall controller for DC fan with dimmable light

Reference	33988
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



Kit de luz black para KLIM E27

Reference	3L022
Voltage (V)	220V-240V
Hertz	50/60Hz
IP	20
Structure material	Steel



TAKI Light kit black SWT 20W dimmable

Reference	3L043
Voltage (V)	220V-240V
Hertz	50/60Hz
IP	20
Structure material	Aluminium

