



Measurements

Surface

XL

A: 276/10.87" A1: 180/7.09" F: ø1600/63"

L

A: 276/10.87" A1: 180/7.09" F: ø1320/52"

S

A: 276/10.87" A1: 180/7.09" F: ø1060/41.7"

Recessed

XL



A: 216/8.5" A1R: 120/4.72"

L

A: 216/8.5" A1R: 120/4.72"

S

A: 216/8.5" A1R: 120/4.72"



Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	20
Power (W)	20
Energy class light source	F
Light source	SMD LED
Lifespan	50.000h
Luminous Flux (lm)	806
Color temperature (K)	2700/ 3000/ 4000K
Light orientation	Direct
CRI	>80
Control System	TRIAC
Structure material	Aluminium
Diffuser material	PMMA
Blade material (fan blades)	Aluminium
Structure finish	Matt Black
RAL/Pantone structure	RAL 9005
Diffuser finish	Opal
Blade finish	Matt Black
Motor type	DC
Fan power (W)	4-6-10-17-24-35
RPM	86-110-140-164-185-210
Airflow (m³/min)	71-95-115-135-158-174
Airflow (CFM)	2524-3355-4052-4785-5584-6147
Sound intensity (dBA)	40-40-43-46-49-52
Maximum decibels	52
Number of blades	3
Maximum tilt (°)	12
Type of control included	0–10V active/passive
Rod diameter	26
Optional rod model	Universal 26mm



Installation instructions



Energy label

