



A	A1	B	C
430/16.93"	220/8.66"	320/12.6"	100/3.94"
D	E	F	G
60/2.4"	130/5.12"	ø1500/59.1"	687/27.05"

Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	44
IK	03
Power (W)	15
Light source	E27 LED
Bulb format	A60
Number of lamp holders	1
Light orientation	Direct
Structure material	Steel
Diffuser material	Glass
Blade material (fan blades)	ABS
Structure finish	Dark Brown
RAL/Pantone structure	RAL8019
Diffuser finish	Opal
Blade finish	Oak
Motor type	DC
Fan power (W)	5-8-12-18-25-35
RPM	73-92-108-127-141-152
Airflow (m³/min)	101-120-138-154-170-187
Airflow (CFM)	3549-4208-4863-5415-5988-6594
Sound intensity (dBA)	29-29-33-36-39-43
Number of blades	3
Maximum tilt (°)	12
Type of control included	Remote control with timer
Fan programming hours	1-4-8h
Rod diameter	26
Optional rod model	Universal 26mm seaside

[Installation instructions](#)

Recommended bulbs



Bulb A60 MAT LED E27 8W 2700K 640Lm	
Reference	17463
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360



Bulb A60 MATE LED E27 8W 3000K CRI90	
Reference	17529
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	810
Color temperature (K)	3000K
Opening angle degrees	360



Bulb A60 MATE LED E27 8W 4000K CRI90	
Reference	17530
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	820
Color temperature (K)	4000K
Opening angle degrees	360

Related accessories



Wall controller white rf applique 6 speeds

Reference	34306
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



Wall controller black rf applique 6 speeds

Reference	34307
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



White wall controller for DC fan with dimmable light

Reference	33987
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



Black wall controller for DC fan with dimmable light

Reference	33988
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass

