



Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	20
Suitable for seaside areas	No
Structure material	Steel
Blade material (fan blades)	Pine Wood
Structure finish	Matt White
RAL/Pantone structure	RAL 9016
Blade finish	Pine
Motor type	DC
Fan power (W)	4-5-7-13-22-32
RPM	58-75-94-124-152-173
Airflow (m³/min)	55-71-96-119-151-174
Airflow (CFM)	1983-2557-3447-4269-5397-6234
Sound intensity (dBA)	29-30-31-33-39-43
Number of blades	3
Type of control included	Remote control with timer
Fan programming hours	1-4-8h
Optional rod model	No dispone



Installation instructions

Measurements


Surface

L

A: 190/7.48" A1: 151/5.94" F: ø900/35.4"

S

A: 190/7.48" A1: 151/5.94" F: ø900/35.4"



Related accessories



Wall controller white rf applique 6 speeds

Reference	34306
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



Wall controller black rf applique 6 speeds

Reference	34307
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



White wall controller for DC fan with dimmable light

Reference	33987
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



Black wall controller for DC fan with dimmable light

Reference	33988
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



White remote control

Reference	34303
IP	20
Structure material	ABS



HEY/HEYWOOD Light kit white SWT 10W dimmable

Reference	3L040
Voltage (V)	220V-240V
Hertz	50/60Hz
IP	20
Structure material	Steel
Opening angle degrees	135

