



Measurements

Surface	
L	
A: 243/9.57"	A1: 223/8.78" F: ø1320/52"
S	
A: 243/9.57"	A1: 223/8.78" F: ø900/35.4"

Recessed	
L	
A: 183/7.2"	A1R: 163/6.42"
S	
A: 183/7.2"	A1R: 163/6.42"

Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	20
Structure material	Steel
Blade material (fan blades)	Pine Wood
Structure finish	Matt Black
RAL/Pantone structure	RAL 9005
Blade finish	Dark Walnut
Motor type	DC
Fan power (W)	4-5-7-13-22-32
RPM	58-75-94-124-152-173
Airflow (m³/min)	55-71-96-119-151-174
Airflow (CFM)	1983-2557-3447-4269-5397-6234
Sound intensity (dBA)	29-30-31-33-39-43
Number of blades	3
Maximum tilt (°)	12
Type of control included	Remote control with timer
Fan programming hours	1-4-8h
Rod diameter	26
Optional rod model	Universal 26mm

Installation instructions



Related accessories



Wall controller white rf applique 6 speeds

Reference	34306
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



Wall controller black rf applique 6 speeds

Reference	34307
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



White wall controller for DC fan with dimmable light

Reference	33987
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass





Black wall controller for DC fan with dimmable light

Reference	33988
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



White remote control

Reference	34303
IP	20
Structure material	ABS



HEY/HEYWOOD Light kit white SWT 10W dimmable

Reference	3L040
Voltage (V)	220V-240V
Hertz	50/60Hz
IP	20
Structure material	Steel
Opening angle degrees	135

