



Measurements


Surface

M

A: 254/10" A1: 190/7.48" F: ø1300/51.2"

S

A: 235/9.25" A1: 173/6.81" F: ø900/35.4"



Recessed

M

A: 194/7.64" A1R: 130/5.12"

S

A: 175/6.89" A1R: 113/4.45"



Mounting	Ceiling
Voltage (V)	220V-240V
Hertz	50/60Hz
Class	I
IP	20
Structure material	Steel
Blade material (fan blades)	ABS
Structure finish	Matt White
RAL/Pantone structure	RAL 9016
Blade finish	Matt White
Motor type	DC
Fan power (W)	5-7-9-13-19-28
RPM	90-115-135-158-185-210
Airflow (m³/min)	80-102-125-143-165-177
Airflow (CFM)	2877-3662-4485-5118-5924-6318
Sound intensity (dBA)	39-40-44-47-51-54
Number of blades	3
Maximum tilt (°)	12
Type of control included	Remote control with timer
Fan programming hours	1-4-8h
Rod diameter	26
Optional rod model	Universal 26mm



Installation instructions



Related accessories



Wall controller white rf applique 6 speeds

Reference	34306
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



Wall controller black rf applique 6 speeds

Reference	34307
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS



White wall controller for DC fan with dimmable light

Reference	33987
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass





Black wall controller for DC fan with dimmable light

Reference	33988
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	ABS + Glass



White remote control

Reference	34303
IP	20
Structure material	ABS



PUNT 2024/TUB Light kit white SWT 18W dimmable

Reference	3L038
Voltage (V)	220V-240V
Hertz	50/60Hz
IP	20
Structure material	Steel
Opening angle degrees	130

