



Mounting	Ceiling
Voltage (V)	100V-240V
Hertz	50/60Hz
Class	I
IP	20
Power (W)	24
Light source	E27 LED
Bulb format	A60
Number of lamp holders	3
Light orientation	Indirect lighting
Cable length	1500 mm
Structure material	Steel
Shade material	Linen
Diffuser material	Papyrus
Structure finish	Matt Black
RAL/Pantone structure	9011
Shade finish	Off White
Diffuser finish	Natural



Installation instructions



Recommended bulbs



Bulb A60 MAT LED E27 8W 2700K 640Lm	
Reference	17463
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	800
Color temperature (K)	2700K
Opening angle degrees	360



Bulb A60 MATE LED E27 8W 3000K CRI90	
Reference	17529
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	810
Color temperature (K)	3000K
Opening angle degrees	360



Bulb A60 MATE LED E27 8W 2200K CRI90	
Reference	17528
Voltage (V)	220V-240V
Hertz	50/60Hz
Power (W)	8
Luminous Flux (lm)	650
Color temperature (K)	2200K
Opening angle degrees	360

Related accessories





KIT track adapter / connector for suspension white

Reference	01997001
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	PC



KIT track adapter /connector for suspension black

Reference	01997002
Voltage (V)	100V-240V
Hertz	50/60Hz
IP	20
Structure material	PC