


## NOCTAMBULE S

Designed by Konstantin Grcic, 2019


F0275000



## NOCTAMBULE S

F0275000

EN



**01. RF0410500** – Power supply kit for Arrangements small & Noctambule

**02. RF0410300** – Led dimmer kit

**03. RF27422** – Ceiling Rose cover Diameter. 185 H. 45

**04. F0253030A** – Suspension attack

**05. RF27498** – Ring led diffuser

**06. RF0254100** – Fixing screws kit

**07. F0254000A** – Low cylinder

**10. F0255000A** – Bowl glass

NOCTAMBULE S F0275000

EN

## RF0410500

POWER SUPPLY KIT FOR ARRANGEMENTS SMALL & NOCTAMBULE



**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off. For the installation of the spare-part, it is necessary to consult a qualified electrician.

©2021 Flos - All rights reserved - [www.flos.com](http://www.flos.com)  
Flos reserves the right to introduce any changes to its own models, without prior notice.

NOCTAMBULE S F0275000

EN

## RF0410500

POWER SUPPLY KIT FOR ARRANGEMENTS SMALL & NOCTAMBULE




Fig.1




Fig.2

Remove the cover.

Disconnect the Vin and Vout terminals from the dimmer using a screwdriver.

**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off. For the installation of the spare-part, it is necessary to consult a qualified electrician.

## RF0410500

POWER SUPPLY KIT FOR ARRANGEMENTS SMALL & NOCTAMBULE




Fig.3



Fig.4

Unscrew the screws (A & B) from the old Power Supply using a screwdriver.

Remove the old Power Supply.

Replace the old Power Supply with the new one.

Now Connect the Vin and Vout terminals to the dimmer using a screwdriver.(Fig.2 page 4)

Fasten back the screws (A & B) of the new Power Supply using a screwdriver.

Place the cover on the ceiling rose. (Fig.1 page 4)


**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off. For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## RF0410300

LED DIMMER KIT



**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## RF0410300

LED DIMMER KIT




Fig.1




Fig.2

Remove the cover.

Disconnect the Vin and Vout terminals from the dimmer using a screwdriver.

**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off. For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

**RF0410300**

LED DIMMER KIT




Fig.3

Unscrew the screws (A) from the old dimmer using a screwdriver.

Remove the old dimmer and replace it with the new one.

Fasten back the screws (A) of the new dimmer using a screwdriver.

Connect the Vin and Vout terminals of the new dimmer using a screwdriver. (Fig.2 page 7)

Place the cover on the ceiling rose. (Fig.1 page 7)

WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

©2021 Flos - All rights reserved - www.flos.com  
Flos reserves the right to introduce any changes to its own models, without prior notice.

NOCTAMBULE S F0275000

EN

## RF27422

CEILING ROSE COVER DIAMETER 185 H.45



WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

©2021 Flos - All rights reserved - [www.flos.com](http://www.flos.com)  
Flos reserves the right to introduce any changes to its own models, without prior notice.

NOCTAMBULE S F0275000

EN

## RF253030A

SUSPENSION ATTACK



WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

©2021 Flos - All rights reserved - [www.flos.com](http://www.flos.com)  
Flos reserves the right to introduce any changes to its own models, without prior notice.

## RF253030A

SUSPENSION ATTACK




Fig.1

Disconnect the cylinders from the ceiling rose.

WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off. For the installation of the spare-part, it is necessary to consult a qualified electrician.

## RF253030A

### SUSPENSION ATTACK




Fig.2




Fig.3

Unscrew the screws from the suspension attack.

Remove the suspension attack from the cylinder.

Connect the new suspension attack to the cylinder.

Tighten the screws to the suspension attack.

Connect the lamp to the ceiling rose.

**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## RF27498

RING LED DIFFUSER



WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

©2021 Flos - All rights reserved - [www.flos.com](http://www.flos.com)

Flos reserves the right to introduce any changes to its own models, without prior notice.

NOCTAMBULE S F0275000

EN

## RF0254100

FIXING SCREWS KIT



WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## F0254000A

LOW CYLINDER



WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

©2021 Flos - All rights reserved - [www.flos.com](http://www.flos.com)

Flos reserves the right to introduce any changes to its own models, without prior notice.

## F0254000A

LOW CYLINDER




Fig.1

Disconnect the cylinders from the ceiling rose.

WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## F0254000A

LOW CYLINDER




Fig.2




Fig.3

Unscrew the screws from the suspension attack.

Remove the suspension attack from the cylinder.

Connect the new suspension attack to the cylinder.

Tighten the screws to the suspension attack.

Connect the lamp to the ceiling rose.

**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## F0254000A

LOW CYLINDER




Fig.4

**Figure 4 and 5 (only for 2/3/4 cylinders version)**

Unscrew the screws from the cylinder (Fig. 4).

Disconnect the cylinder from the other one (Fig. 5).

Replace the old cylinder with the new one.

**Now assemble all the components, please proceed in reverse order.**

Connect the cylinders.

Tighten the screws to the cylinder.

Connect the suspension attack to the cylinder.

Tighten the screws to the suspension attack.




Fig.5

Connect the lamp to the ceiling rose.

**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## F0255000A

BOWL GLASS



WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

## F0255000A

BOWL GLASS




Fig.1

Disconnect the cylinders from the ceiling rose.

WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## F0255000A

BOWL GLASS




Fig.2




Fig.3

Carefully place the lamp in a horizontal position by resting it on the cylinder packages.

Unscrew the screws from the suspension attack.

Remove the suspension attack from the cylinder.

**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## F0255000A

BOWL GLASS




Fig.4




Fig.5

**Figure 4 and 5 (only for 2/3/4 cylinders version)**

Connect the cylinder to the other one (3).

Tighten the screws to the cylinder (1-2).

WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.

NOCTAMBULE S F0275000

EN

## F0255000A

BOWL GLASS




Fig.6




Fig.7

Unscrew the screws from the bowl (Fig. 6).

Disconnect the cylinder from the bowl (Fig. 7).

Remove the old bowl and place the new one.

Connect the cylinder to the new bowl.

Tighten the screws to the new bowl.

**Now assemble all the components, please proceed in reverse order.**

Connect the suspension attack to the cylinder.

Tighten the screws to the suspension attack.

Connect the lamp to the ceiling rose.

WARNING! When installing and whenever acting on the appliance, ensure that the power supply has been switched off.  
For the installation of the spare-part, it is necessary to consult a qualified electrician.