

FLOS

F018D25AU13 Pale Green

In Vitro Suspension

Designed by Philippe Starck, 2020



Hanging version. Light source included. 110–277V ON/OFF or dimmable electrical power integrated within the dedicated ceiling attachment. Hanging cable length 1000 mm.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

| | |
|------------------------|----------------------|
| EAN | 8054793316130 |
| Mounting | Suspension |
| Environments | Outdoor wet location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | Edge Lighting |
| Number of lamps | 1 |
| System power (W) | 13 |
| System flux (lm) | 799 |

Physical

| | |
|---------------------|------------|
| Color | Pale Green |
| Orientation | Fixed |
| Cord color | Black |
| Net weight (lb) | 10.06 |
| Package height (in) | 9.25 |
| Package width (in) | 25.79 |
| Package length (in) | 15.16 |
| Package volume (in) | 3616.34 |
| IP internal | 66 |



Download

Family spec sheet [ZIP](#)
Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Ecodesign and Energy Labelling


This product contains a light source of energy efficiency class F




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



Schematic light drawing



Photometric

| | |
|------------------------|-----------|
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 111 |
| Beam angle C90-270 (°) | 111 |
| Extreme cut off | No |

Electrical

| | |
|--------------------|------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 110-277 |
| Driver | Integrated |
| Emergency type | No |

Notes

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.


For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Accessories & Power Supply



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)