

FLOS


09.8220.DX Matte Rust

Oblique Floor ONLINE EXCLUSIVE

Designed by Vincent Van Duysen

LED - Top LED - 8W - 479lm - 2700K - CRI> 90 - Beam° 34

Designer Vincent Van Duysen reinterprets his Oblique table light into a floor lamp. Launched in 2020, the table lamp created a new way of diffusing and enjoying light, provided by innovative, Flos-developed technology. While traditional reading lamps require a tilted head to spotlight a focused area, Oblique is engineered with a combination of LEDs and lenses that requires only a small amount of space to produce an extremely bright beam of light that falls "obliquely" from the head of the lamp onto the lit surface. The resulting beam is powerful and controlled yet asymmetrical, ideal for illuminating a work area or your favorite novel. Key features An integrated USB-C port charger in the base charges additional devices. Round flat head for minimal visual intrusion A patented ultra-flat lens with very high efficiency of 97%



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Floor
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	8
System power (W)	10
System flux (lm)	479

Physical

Color	Matte Rust
IP internal	20

Download

Mounting instructions [Download PDF](#)

Photometric Files


LDT / IES [Download ZIP](#)

Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user



Schematic light drawing



Beam Angle: 35°		
h(m)	E(lx)	D(m)
1	229	2.18
2	57	4.36
3	25	6.54
4	14	8.72
5	9	10.90

Luminous flux luminaire
479 lm

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	46

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Forward voltage (V)	24
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmer on board
Dimming range (%)	1-100
Precabled	Yes
Plug type	Twist and Lock