


INSTALLATION INSTRUCTIONS

Squire Cube Series Item Nos. GLHP564630 | GLHP578762

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER

Fig. 1



HANGING THE FIXTURE (Fig. 1)

1. Shut off the power at the circuit breaker and remove the old fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Attach the mounting plate (B) to the outlet box (not supplied) with mounting screws (A). Ground Wire must face out.

CONNECTING THE WIRES (Fig. 2).

4. Connect the electrical wires as shown in Fig.2. Making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the circular strap using the green screw provided.

COMPLETING THE INSTALLATION (Fig.1)

5. Align the fixture (D) to mounting plate (B) and secure with screws (E) .
6. To prevent moisture from entering the outlet box and causing a short, use clear caulking (i.e. Indoor/Outdoor Silicone Sealant) to outline the outside of fixture back. plate where it meets the wall leaving a space at bottom to allow moisture a means to escape. (Fig. 3)
7. The fixture can switch between three color temperatures(3500K-3000K-2700K),which can be adjusted to your preference with the switch at the bottom(Fig.4)

Fig. 2



Fixture Wires	House Wires
Black or Smooth	Black (Hot)
White or Ribbed	White (Neutral)
Bare wire (Ground)	Green or Bare Copper (Ground)

Your installation is now complete. Return power to the junction box and test the fixture.

Fig.3 Sealing




Fig.4

