Carson Pendant

KP1084, KP1092, KP1104, KP1114

GENERATION LIGHTING PENDANT

GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.

This product may be dimmed with an electronic dimmer.

This instruction shows a typical installation.

CAUTION - RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°c supply conductors.

SAVE THESE INSTRUCTIONS!



GENERATION LIGHTING 7400 Linder Ave., Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 www.generationlighting.com

Install the Fixture



- Secure the mounting plate to the junction box.
- 2 Screw the half ball to the stem which will be on top.
- 3 Determine the wanted height or look of the fixture with the provided stems, then assemble them by screwing them together, do not include half ball/stem assembly.
- 4 Feed the fixture wires through the stem assembly, then screw the stem assembly to the fixture.
- 5 Feed the fixture wires through collar nut, canopy, and the half ball assembly, then screw the half ball assembly onto the stem assembly.
- 6 Slide the half ball assembly onto the screw collar on the mounting plate.
- 7 Connect the negative (-) fixture wire to the negative (-) output driver wire with a wire nut.
- 8 Connect the positive (+) fixture wire to the positive (+) output driver wire with a wire nut.
- 9 Connect the fixture to a suitable ground in accordance with local electrical codes.
- Connect the white input driver wire to the neutral power line wire with a wire nut.
- Connect the black input driver wire to the hot power line wire with a wire nut.
- Neatly place all the wires into the canopy/junction box, place the canopy onto the mounting plate and secure it in place by screwing the collar nut tightly onto the mounting plate.