

VL RING CROWN 1

Designed by Vilhelm Lauritzen



Description

The pendant emits light directed primarily downwards. The opal glass provides a comfortable and uniform illumination of the area around the fixture.

Variants

| VARIANT NUMBER | COLOR, RAL | W / H / L (IN) / W (LB) |
|----------------|-------------------------|------------------------------|
| 5741925423 | BRASS/GLOSSY OPAL GLASS | 7.5 / 13.5 / 7.5 IN / 3.4 LB |

Materials & Finishes

MATERIALS

Shades: Hand blown, 3-layered, polished opal glass. Suspension: Untreated brass, will patinate.

FINISHES

Glossy, hand blown white opal glass. Satin polished brass, untreated.

Mounting

Mounting: Canopy: White. Cord type: 2-conductor, 18 AWG cloth-covered power cord. Cord length: 12 feet. For mounting instructions, see download section on the product detail page.

Information

Electrical:

System Wattage: 15W

LED Wattage: 14 W

Delivered lumens: 936

Efficacy: 62.4 lm/W -

Certifications:

cULus, Dry Location


Protection class IP20

Controllability: Phase dimming


Actual performance dependent upon screw-base lamp used. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Light distribution diagrams


CARTESIAN



ISOLUX



POLAR



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

| VARIANT NO. | LIGHT SOURCE | VOLTAGE/FRQ | LUMEN | FEATURES | CABLE |
|-------------|-----------------|-------------|-------|----------|---------------|
| 5741925423 | A-19/ medium US | 120V | 936 | - | White textile |