


PANTHELLA 160 PORTABLE

Designed by Verner Panton



Description This portable table lamp emits a glare-free, soft, and comfortable light. The metal shade variants reflects the light downwards and provides pleasant illumination created by the inner white painted shade and the reflection from the trumpet-shaped stem. The opal acrylic variants provides gentle illumination and subtle ambience due to the transparency and the reflection of the downward light on the inner side of the shade.

Variants	VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
	5744162924	PALE ROSE	6.3 / 9.4 / 6.3 IN / 0.9 LB
	5744166768	WHT OPAL ACRYL, 970	6.3 / 9.4 / 6.3 IN / 0.9 LB
	5744168070	GREY OPAL ACRYL	6.3 / 9.4 / 6.3 IN / 0.9 LB
	5744612571	BLK, 708	- / - / - IN / 0.9 LB
	5744612584	ORANGE, 269	6.3 / 9.4 / 6.3 IN / 0.9 LB
	5744612607	WHT, 011	- / - / - IN / 0.9 LB
	5744612610	PALE BLUE	6.3 / 9.4 / 6.3 IN / 0.9 LB
	5744612623	CORAL	6.3 / 9.4 / 6.3 IN / 0.9 LB

Materials & Finishes **MATERIALS**
Shade: Deep-drawn steel or injection-molded opal-gray acrylic or white-opal acrylic.
Base and housing: Die-cast aluminum.

FINISHES

White Opal Acrylic shade with white stand.
Grey Opal Acrylic shade with high lustre chrome stand.
Pale Rose, Pale Blue or Coral, powder coated.

Mounting


Cable length: 4.9ft. Power: USB cable or Qi base for standard USB-A adapter. Light control: Switch on base. Battery lifetime: 5 hours @ 100%. Step-dim: 0%/10%/33%/100% For mounting instructions, see download section on the product detail page.

Information


Please note that Panthella Portable comes with a USB cable but without an adapter and Qi charger. A separate USB adapter is available as an accessory. Compatible with standard USB adapters (Min. 1.5A) and Qi wireless chargers.
White cord for White Opal and Pale Rose variants. Black cord for other variants. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Light distribution diagrams


CARTESIAN



ISOLUX



POLAR



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
5744162924	LED 2700K		81	-	Wht
5744166768	LED 2700K		81	-	Wht
5744168070	LED 2700K		81	-	Blk
5744612571	LED 2700K		81	-	Blk

louis poulsen

5744612584	LED 2700K	81	-	Blk
5744612607	LED 2700K	81	-	Wht
5744612610	LED 2700K	81	-	Blk
5744612623	LED 2700K	81	-	Blk
