

PH LOUVRE

Designed by Poul Henningsen



Description

The fixture provides 100% glare-free light. The geometrical, spherical design is based on the principle of illuminating all surfaces at the same angle. This ensures uniform light around the fixture, illuminating both walls and ceiling. Matte painted undersurfaces and glossy top surfaces result in an attractive reflection of the diffused light, creating uniform light distribution around the fixture.

Variants

VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
5741917910	WHT, 015	23.6 / 25.6 / 23.6 IN / 22.0 LB
5741917923	WHT, 015	23.6 / 25.6 / 23.6 IN / 22.0 LB

Materials & Finishes

MATERIALS

Shades: Spun aluminum. Frame: High lustre chrome plated, extruded brass. Housing: High lustre chrome plated, spun aluminum.

FINISHES

White, wet painted.

louis poulsen

Mounting


Suspension type: 1x stainless steel aircraft cable. Canopy: White. Cord type: 3-conductor, 18 AWG white PVC power cord. Cord length: 12'. For mounting instructions, see download section on the product detail page.

Information


Electrical:
 System Wattage: 97W
 LED Wattage: 89 W
 Delivered lumens: 2,479 - 2,596
 Efficacy: 25.6 lm/W - 26.8 lm/W
 Certifications:
 cULus, Dry Location
 Protection class IP20
 Controllability: 0-10V Dimming
 Color Rendering: Ra≥90 For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Light distribution diagrams


CARTESIAN



ISOLUX



POLAR



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
5741917910	LED 2700K (ra90)	120-277V/60HZ	2596	Dim 0-10v	Wht
5741917923	LED 3000K (ra90)	120-277V/60HZ	2596	Dim 0-10v	Wht