

TOLDBOD 6.1 WALL

Designed by Louis Poulsen A/S



Description

The light is directed 100% downwards and the shade has a matte white painted interior emitting a soft, diffused, comfortable light.

Variants

VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
5743911723	NAT PAINT ALU, 162	6.1 / 6.2 / 10.5 IN / 2.6 LB
5743911736	BLK, 723	6.1 / 6.2 / 10.5 IN / 2.6 LB

Materials & Finishes

MATERIALS

Shield: Tempered sand blasted glass. Wall plate: Die cast aluminum. Luminaire head: Die cast aluminum. Arm: Extruded aluminum.

FINISHES

Black or natural painted aluminum, powder coated.

Mounting

Surface: Mounted directly to finished surface over a recessed 4" octagonal junction box. For mounting instructions, see download section on the product detail page.

Information

Electrical:
System Wattage: 10 W
Delivered lumens: 189 lm
Efficacy: 18.9 lm/W
Certifications:
cULus, Wet Location
Protection class IP44
IK class 05
BUG Rating: B1-U2-G1
Controllability: Phase dimming
Min.-Max. Ambient Temp: -20°C to +40°C
Actual performance dependent upon screw-base lamp used. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Light distribution diagrams

CARTESIAN



ISOLUX



POLAR



BUG



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
5743911723	G16.5/IF candelabra	120V	2093	-	-
5743911736	G16.5/IF candelabra	120V	2093	-	-
