NYHAVN WALL

Nyhavn Wall - 5743200117

The conical shade ensures comfortable light that is directed downwards in a wide beam. The shade interior has a white matt painted surface, ensuring uniform light distribution. The rings ensure that a stray light is controlled, and direct a small amount of light onto the top side of the shade for self-illumination.

Skagen

Fuchu City Junior High School No. 3

Product info

Environmental Product Specification

This product is compliant with the requirements contained in the European Directives, RoHS Directive 2011/65 and 2015/863. This product is designed so that 100% of the product can be disassembled and reused.

Information

Please note that the copper versions are untreated in order to achieve a verdigris finish over time. This can result in an inconsistent surface finish prior to the product achieving full patina.

Mounting

Terminal block: 1x3x2.5mm². Cable entries: 2x bottom + 3x rear entries for Ø 10-14.5mm cable. Looping: Approved, max. 3x1,5mm².

Finish

Copper, brushed or white, wet painted.

Materials

Shades: Spun aluminium or spun copper. Enclosure: Clear glass. Top: Spun aluminium or spun copper. Wall box: Die cast aluminium. Wall box cover: Spun aluminium or spun copper. Arm: Copperplated, red brass or steel.

Sizes and weights

Width x Height x Length (mm) | 310 x 225 x 445 Max 4.2 kg

Class

Ingress protection IP44. Electric shock protection I w. ground.

Specification notes

The innovation of light sources is ongoing. Consequently we only inform about the max. wattages. On www.louispoulsen.com we update a list of recommendable light sources.

Light source

1x100W E27

Information

Please note that the copper versions are untreated in order to achieve a verdigris finish over time. This can result in an inconsistent surface finish prior to the product achieving full patina.

Light distribution diagrams

Cartesian

Isolux

Polar

Spare parts & accessories

Product	Variant number
Nyhavn Wall glass clear	5743590513
Nyhavn Wall Glass, partly frosted	5743590526
Nyhavn screw f/glass	5743590539
Nyhavn Wall/Pendant gasket	5743590555

Data specifications

Colour	**Brushed copper**	Length	**445**
Width	**310**	Height	**225**
IP class	**44**	IK class	**-**
Class	**I**	Net Weight	**4.2**
Wind Load (m2)	**-**	Standby (W)	**-**
Power Factor (P = 100 % / P = 50 %)	**-**	Inrush Current	**-**
Light source	**1x100W E27**	Kelvin	**-**

CRI	-
Lumen	-
Efficacy	-
Min. Dim Level (%)	-
BUG Rating	**B0 U2 G0**
Driver life	-

SDCM	-
Watt	-
Light control	-
Surge Protection	-
L80B50 (hours)	-