


# WOODY

## FR-W1814-72L

72" Ceiling Fan

# MODERN FORMS

## SMART FANS



### PRODUCT DESCRIPTION

With sturdy blades crafted from solid wood- properly treated to weather the outdoors- this smart fan is rugged refinement to the core. Take control of it with our exclusive Modern Forms app- features like Adaptive Learning make life easier every day by suggesting optimized schedules, while a powerful DC motor inside keeps things running smooth, quiet and up to 70% more efficient than traditional AC fans. Choose a bronze housing with dark walnut wood, matte black with distressed koa or graphite with weathered gray.

### FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes BT remote control
- Optional wall control (F-WCBT-WT) sold separately
- Compatible with Modern Forms app

### AIRFLOW/ENERGY EFFICIENCY

<b>Weighted-Average/High Airflow CFM:</b>	7690/10546
<b>Weighted-Average/High Energy Use (W):</b>	34/51
<b>Estimated Yearly Energy Cost (\$):</b>	10
<b>Weighted-Average/High Efficiency (CFM/W):</b>	227/310
<b>Max RPM:</b>	112

### ORDER NUMBER

Model	Housing	Blade
<b>FR-W1814-72L</b>	<b>BZ</b> <i>Bronze</i>	<b>DW</b> <i>Dark Walnut</i>
	<b>GH</b> <i>Graphite</i>	<b>WG</b> <i>Weathered Gray</i>
	<b>MB</b> <i>Matte Black</i>	<b>DK</b> <i>Distressed Koa</i>

Example: **FR-W1814-72L-GH/WG**

For 2700K add "-27" ; for 3500K add "-35" before the finish: **FR-W1814-72L27GHWG**

**\*Results may vary based on application and surroundings.**

**\*This fan comes uni-pack - blade select options are not available**

The Modern Forms app synchronizes seamlessly with smart home devices you already own



modernforms.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

### SPECIFICATIONS

<b>Construction:</b>	Aluminum, Balsa Wood
<b>Blade:</b>	15° Pitch, 72" sweep
<b>Downrod:</b>	3/4"W X 4.5"H
<b>Mounting Slope:</b>	Up to 30°
<b>Wire:</b>	80"
<b>Hanging Weight:</b>	20 lbs
<b>Total Power:</b>	60W
<b>Standards:</b>	UL/cUL Wet Location listed, Title 24 JA8-2016 Compliant, Title 20
<b>Motor Type:</b>	125 x 25 sensorless DC motor

### WIRELESS PERFORMANCE

<b>Wi-Fi Range:</b>	Up to 150 ft*
<b>Bluetooth Range:</b>	Up to 150 ft*

### LUMINAIRE PERFORMANCE

<b>Light Source:</b>	LED
<b>Light Wattage:</b>	20W
<b>Lumens/Delivered Lumens:</b>	1600/846
<b>Dimming:</b>	Integrated
<b>CRI:</b>	90
<b>Color Temperature:</b>	3000K (2700K/3500K options available)
<b>Rated Life:</b>	50,000 hours

**OPTIONAL ACCESSORIES**

<p>Bluetooth Wall Control</p>		<p><b>F-WCBT</b></p>	<p><b>WT</b> White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.</p>
<p>Bluetooth Remote Control</p>		<p><b>F-RCBT</b></p>	<p><b>WT</b> White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.</p>
<p>Downrod</p>		<p><b>XF-12</b> 12IN  <b>XF-18</b> 18IN  <b>XF-24</b> 24IN  <b>XF-36</b> 36IN  <b>XF-48</b> 48IN  <b>XF-60</b> 60IN  <b>XF-72</b> 72IN</p>		<p>All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p>
<p>Downrod Couplers</p>		<p><b>XF-I</b></p>		<p>Connects two downrods together.</p>
<p>Sloped Ceiling Kit</p>		<p><b>XF-SCK</b></p>		<p>Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.</p>

Examples: Wall Control: **F-WCBT-WT**, Remote Control: **F-RCBT-WT**, Downrod: **XF-12-BN**, Downrod Coupler: **XF-I-MB**, Sloped Ceiling Kit: **XF-SCK-MW**

**SUGGESTED DOWNROD HEIGHT USAGE**

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

**SLOPED CEILING DEGREE CONVERSION CHART**

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire