



PRODUCT DESCRIPTION


Elongated tubes of LED light are housed in incredibly small 1" diameter aluminum and suspended by nearly invisible support cables. Engineered to connect the various lengths end-to-end or with use of the rigid, angled adapters, adds endless applications for creativity and function. Each length includes a power feed within a surface mounted canopy and non-electrical support cables that standoff using ceiling anchors. With no additional power source components required, the continuous run pendants in this series are a welcome convenience for commercial applications. Lengths range from 36" to impressive 96" long. Individually, the fixtures provide ample lighting downward with minimal disruption to the architectural sight lines of a space. Available in Black, White, and brushed Aluminum finishes these are exemplary streamlined forms with functional purpose.

MEASUREMENTS

DIMENSION : 93.7" L x 1.5" W x 1.25" H  
MAX OAH : 121" OAH  
CANOPY : 4.5" W x 1.25" H x 16" L  
HANGING WEIGHT : 6.5 lb

LAMPING

INPUT VOLTAGE : 120-277V  
LUMENS : 5,250 Rated (4,200 Del.)  
BULB : 1 x 68W LED PCB Integrated , 68W Total  
BULB INCLUDED : (Integrated)  
DIMMABLE : 30-35-40  
CRI : 90 CRI  
COLOR\_TEMP : Select 30/35/40K



\*max overall height

FINISHES OPTION

- Black (BK)
- Satin Aluminum (SA)
- White (WT)

GLASS

Frosted 90

MATERIAL

Acrylic, Aluminum

RATINGS

cETLus  
Dry Location



ADDITIONAL

RATED LIFE 50000 Hours  
OPERATING TEMPERATURE:  
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Contemporary  
Lighting™

WESTERN DISTRIBUTION CENTER (HEADQUARTER)  
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746  
EASTERN DISTRIBUTION CENTER  
101 GARDNER PARK | PEACHTREE CITY, GA 30269  
P. 626.956.4200 | F. 626.956.4225 | maximlighting.com